

Stripwound flexible metal hose, AISI 304 e 316L stainless steel interlocked for electrical cable protection telephone wirings and optical fiber

Tipo DOU double overlap, unpacked – UNI EN ISO 15465:2005

CLASSIFICATION	UNI CEI EN 61386
Resistance to compression	5
Resistance to impact	5
Lower temperature -40 °C	5
Upper temperature +600 °C	6
Bending	High flexibility
Electrical characteristics	maintain electrical continuity and EMC shielding
IP protection according CEI EN 60529	IP40
Corrosion resistance	Higt
Tensile strength up to Ø 40 mm	4
Tensile strength from > Ø 40	5
Flame propagation	Non-flame propagating
Suspended load capacity	Variabile in funzione del Ø (valore 3 - 5)
RoHS – REACH compliant	Yes
Material type	Acciaio INOX AISI 304 - 316L UNI 10088-1
Made in European Union	Yes



# ZDXF technical data sheet

OMMC ITALFLEX Srl  
Via Pian di Rocco, 22  
16042 CARASCO (GE) - ITALY  
Ph. +39 0185 350231 | Fax +39 0185 351240



[sales@ommcitalflex.com](mailto:sales@ommcitalflex.com)



CODE	Int. Ø mm	Ext. Ø mm	Material	Bending mm	Weight Kg/m
ZDX10004	4,0	6,0	304	21	0,06
ZDX1000405	4,5	7,5	304	23	0,06
ZDX10005	5,0	7,0	304	25	0,07
ZDX10005B	5,0	7,4	304	19	0,09
ZDX10005450775	5,5	7,9	304	20	0,09
ZDX10006	6,0	8,4	304	22	0,1
ZDX100608	6,0	8,0	304	29	0,08
ZDX1000609	6,0	9,0	304	34	0,1
ZDX10007	7,0	9,4	304	25	0,11
ZDX1000709	7,0	9,0	304	33	0,09
ZDX10007010	7,0	10,0	304	38	0,12
ZDX10008	8,0	11,0	304	43	0,13
ZDX10009	9,0	12,0	304	47	0,15
ZDX10010	10,0	13,0	304	34	0,15
ZDX10012	12,0	15,0	304	40	0,18
ZDX10013	13,0	16,0	304	43	0,19
ZDX10014	14,0	17,0	304	46	0,21
ZDX10015	15,0	18,6	304	56	0,22
ZDX1001505	15,5	19,1	304	58	0,23
ZDX10016	16,0	19,6	304	59	0,24
ZDX10018	18,0	21,6	304	66	0,26
ZDXF10020	20,0	23,6	304	73	0,29
ZDXF1002005	20,5	24,1	304	74	0,3
ZDXF10022	22,0	25,6	304	79	0,32
ZDXF10025	25,0	28,6	304	89	0,36
ZDXF1002605	26,5	29,1	304	93	0,37
ZDXF10032	32,0	36,5	304	118	0,62
ZDXF10033	33,0	37,5	304	122	0,64
ZDXF10035	35,0	39,5	304	129	0,68
ZDXF10040	40,0	44,5	304	146	0,77
ZDXF1005005	50,5	55,0	304	182	0,96
ZDX40004	4,0	6,0	316L	21	0,06
ZDX40005	5,0	7,0	316L	25	0,07
ZDX40006	6,0	8,4	316L	30	0,08
ZDX40007	7,0	9,4	316L	34	0,09

Packaging: [1] carton box [2] reel at specific measure [3] cutted at custom length [4] cutted with assembled fittings

OMMC ITALFLEX Srl | [www.ommcitalflex.com](http://www.ommcitalflex.com)